

Item # PK2913-02BA, Stepper Motor

SPECIFICATIONS

Motor Type	2-Phase
Frame Size	3.35 in
Motor Length	4.96 in.
Speed-Torque Characteristics	 Speed - Torque Characteristics
Holding Torque	Bipolar (Series) 1320 oz-in Unipolar 930 oz-in
Shaft/Gear Type	Round Shaft (No Gearhead)
Shaft	Double
Type	Standard
Encoder	Not Equipped
Basic Step Angle	1.8°

Radial Load	0 in. from Shaft End = 58 lb 0.2 in. from Shaft End = 65 lb 0.39 in. from Shaft End = 76 lb 0.59 in. from Shaft End = 87 lb 0.79 in. from Shaft End = 108 lb
Axial Load	13.5 lb

Output Step Angle	1.8 °
Electromagnetic Brake	Not Equipped
Motor Connection Type	Flying Leads
Connection Type	Bipolar (Series) Unipolar
Current per Phase (A/phase)	2.8 [Bipolar (Series)] 4 [Unipolar]
Lead Wires	6
Voltage (VDC)	5.3 [Bipolar (Series)] 3.8 [Unipolar]
Resistance (Ω/phase)	1.94 [Bipolar (Series)] 0.97 [Unipolar]
Inductance (mH/phase)	16.8 [Bipolar (Series)] 4.2 [Unipolar]
Rotor Inertia	22 oz-in ²
RoHS Compliant	Yes
Insulation Resistance	100 M Ω or more when 500 VDC megger is applied between the windings and the case under normal ambient temperature and humidity.
Dielectric Strength	Sufficient to withstand 1.0 kVAC at 50 Hz or 60 Hz applied between the windings and the case for 1 minute under normal ambient temperature and humidity.
Temperature Rise	Temperature rise of the windings is 176°F (80°C) or less measured by the change resistance method. (at rated voltage, at standstill, 2 phases energized)
Insulation Class	Class B [266°F (130°C)]
Ambient Temperature Range	14 ~ 122°F (-10 ~ 50°C) (non-freezing)
Ambient Humidity	85% or less (non-condensing)
Shaft Runout	0.05 mm (0.002 in.) T.I.R.
Concentricity	0.075 mm (0.003 in.) T.I.R.
Perpendicularity	0.075 mm (0.003 in.) T.I.R.
Radial Play	0.025 mm (0.001 in.) maximum of 5 N (1.12 lb.)
Axial Play	0.075 mm (0.003 in.) maximum of 10 N (2.2 lb.)
Step Accuracy	±3 arc minutes (±0.05°)

Radial Load

0 in. from Shaft End = 58 lb
0.2 in. from Shaft End = 65 lb
0.39 in. from Shaft End = 76 lb
0.59 in. from Shaft End = 87 lb
0.79 in. from Shaft End = 108 lb

Axial Load

13.5 lb